

Indoor housings

for flat panels

The indoor housings are the perfect way to protect and brand your flat panel



Audipack®

It's great to have solutions...

Screens

in public places



Screens mounted in public places demand protective solutions.

The Audipack lockable indoor housings offer heavy-duty protection for the flat panel, and a sleek, modern look that does not detract from the screen content.

The indoor theft delay housing is a security housing for digital signage projects. A fully removable front with hardened glass protects the monitor.

It is available in portrait or landscape models.


The stylish glass front is made from polished, coated and hardened glass and the housing also offers internal space for equipment such as players and switchers.

Slim-line indoor theft delay housings are also available for LCD and LED screens with a reduction in depth of 50% to complement thinner panels.

- ▲ **Suitable for any brand and type of flat panel**
- ▲ **Very easy installation**
- ▲ **Easy equipment and flat panel access**
- ▲ **Available in Any RAL colour and finishing**



(FSMT-70) The flat panel is very easy accessible



High level finishing



Easy access after unlocking the glass front



Optional available in any RAL colour

Slim-line THEFT DELAY HOUSINGS

For screens up to 75 mm. depth

Max. brightness: 700 cd/m²

IP 30



Colour: **Black bezel, white housing, glass front**

	Landscape	Portrait		
Ref.	FSMT-32S	FSMT-32SP		Max. ° 32
Max. screen size	W 800 x D 75 x H 500	W 500 x D 75 x H 800		
Ref.	FSMT-40S	FSMT-40SP		Max. ° 40
Max. screen size	W 990 x D 75 x H 600	W 600 x D 75 x H 990		
Ref.	FSMT-42S	FSMT-42SP		Max. ° 42
Max. screen size	W 1035 x D 75 x H 630	W 630 x D 75 x H 1035		
Ref.	FSMT-46S	FSMT-46SP		Max. ° 46
Max. screen size	W 1120 x D 75 x H 675	W 675 x D 75 x H 1120		
Ref.	FSMT-47S	FSMT-47SP		Max. ° 47
Max. screen size	W 1145 x D 75 x H 690	W 690 x D 75 x H 1145		
Ref.	FSMT-49S	FSMT-49SP		Max. ° 49
Max. screen size	W 1200 x D 75 x H 710	W 710 x D 75 x H 1200		
Ref.	FSMT-50S	FSMT-50SP		Max. ° 50
Max. screen size	W 1210 x D 75 x H 725	W 725 x D 75 x H 1210		
Ref.	FSMT-55S	FSMT-55SP		Max. ° 55
Max. screen size	W 1320 x D 75 x H 785	W 785 x D 75 x H 1320		
Ref.	FSMT-60S	FSMT-60SP		Max. ° 60
Max. screen size	W 1435 x D 75 x H 855	W 855 x D 75 x H 1435		
Ref.	FSMT-65S	FSMT-65SP		Max. ° 65
Max. screen size	W 1530 x D 75 x H 905	W 905 x D 75 x H 1530		

CLASSIC THEFT DELAY HOUSINGS

Max. brightness: 700 cd/m²

Optional: non-reflective glass bezel

IP 30



Colour: **Black bezel, white housing glass front**

	Landscape	Portrait		
Ref.	FSMT-32	FSMT-32P		Max. ° 32
Max. screen size	W 800 x D 150 x H 500	W 500 x D 150 x H 800		
Ref.	FSMT-40	FSMT-40P		Max. ° 40
Max. screen size	W 990 x D 150 x H 600	W 600 x D 150 x H 990		
Ref.	FSMT-42	FSMT-42P		Max. ° 42
Max. screen size	W 1035 x D 150 x H 625	W 625 x D 150 x H 1035		
Ref.	FSMT-46	FSMT-46P		Max. ° 46
Max. screen size	W 1120 x D 150 x H 675	W 675 x D 150 x H 1120		
Ref.	FSMT-47	FSMT-47P		Max. ° 47
Max. screen size	W 1145 x D 150 x H 690	W 690 x D 150 x H 1145		
Ref.	FSMT-49	FSMT-49P		Max. ° 49
Max. screen size	W 1200 x D 150 x H 710	W 710 x D 150 x H 1200		
Ref.	FSMT-50	FSMT-50P		Max. ° 50
Max. screen size	W 1210 x D 150 x H 725	W 725 x D 150 x H 1210		
Ref.	FSMT-55	FSMT-55P		Max. ° 55
Max. screen size	W 1320 x D 150 x H 785	W 785 x D 150 x H 1320		
Ref.	FSMT-60	FSMT-60P		Max. ° 60
Max. screen size	W 1435 x D 150 x H 855	W 855 x D 150 x H 1435		
Ref.	FSMT-65	FSMT-65P		Max. ° 65
Max. screen size	W 1530 x D 150 x H 905	W 905 x D 150 x H 1530		
Ref.	FSMT-70	FSMT-70P		Max. ° 70
Max. screen size	W 1645 x D 115/145 x H 975	W 975 x D 115/145 x H 1645		
Ref.	FSMT-72	FSMT-72P		Max. ° 72
Max. screen size	W 1695 x D 115/145 x H 1000	W 1000 x D 115/145 x H 1695		
Ref.	FSMT-75	FSMT-75P		Max. ° 75
Max. screen size	W 1750 x D 115/145 x H 1030	W 1030 x D 115/145 x H 1750		
Ref.	FSMT-80	FSMT-80P		Max. ° 80
Max. screen size	W 1875 x D 115/145 x H 1100	W 1150 x D 115/145 x H 1865		


Screens in shops

FSMI housings with open front are suitable for installing screens in shop window environments. The open front structure allows to extract the heat radiation from the screen without using forced ventilation.

FSMI housing can be installed to 700 and 900 series floorstands and to the ceiling to floor CTF systems.

In combination with the ACG air curtain, the heat radiation of the shop window can be cooled down.



Slim-line INDOOR HOUSINGS OPEN	INDOOR HOUSINGS OPEN		NEW	
	Landscape	Portrait		
Max. brightness: 700 cd/m² Ideal for retail areas  Colour: Black bezel, white housing, open front bezel, no glass	Ref.	FSMI-32S	FSMI-32SP	
	Max. screen size	W 800 x D 75 x H 500	W 500 x D 75 x H 800	Max. ° 32
	Ref.	FSMI-40S	FSMI-40SP	
	Max. screen size	W 990 x D 75 x H 600	W 600 x D 75 x H 990	Max. ° 40
	Ref.	FSMI-42S	FSMI-42SP	
	Max. screen size	W 1035 x D 75 x H 630	W 630 x D 75 x H 1035	Max. ° 42
	Ref.	FSMI-46S	FSMI-46SP	
	Max. screen size	W 1120 x D 75 x H 675	W 675 x D 75 x H 1120	Max. ° 46
	Ref.	FSMI-47S	FSMI-47SP	
	Max. screen size	W 1145 x D 75 x H 690	W 690 x D 75 x H 1145	Max. ° 47
Ref.	FSMI-49S	FSMI-49SP		
Max. screen size	W 1175 x D 75 x H 705	W 705 x D 75 x H 1175	Max. ° 49	
Ref.	FSMI-50S	FSMI-50SP		
Max. screen size	W 1205 x D 75 x H 725	W 725 x D 75 x H 1210	Max. ° 50	
Ref.	FSMI-55S	FSMI-55SP		
Max. screen size	W 1320 x D 75 x H 785	W 785 x D 75 x H 1320	Max. ° 55	
Ref.	FSMI-60S	FSMI-60SP		
Max. screen size	W 1435 x D 75 x H 855	W 855 x D 75 x H 1435	Max. ° 60	
Ref.	FSMI-65S	FSMI-65SP		
Max. screen size	W 1535 x D 75 x H 910	W 910 x D 75 x H 1535	Max. ° 65	

ACCESSORIES

UNIPLATFIX PRO (UNIVERSAL FLAT PANEL BRACKETS)



Lock the bracket with the optional lock
Ref.: 230052

Ref.
Dimensions in mm
Max. mounting range in mm
Min. mounting range in mm



UFPRO-V400
W 430 x D 6 x H 430
W 400 x H 400
W 100 x 100



UFPRO-0500
W 516 x D 32 x H 382
W 470 x H 360
W 125



UFPRO-0700
W 716 x D 32 x H 502
W 670 x H 446
W 125



UFPRO-0800
W 860 x D 32 x H 502
W 810 x H 446
W 130



UFPRO-0801
W 860 x D 39 x H 727
W 810 x H 671
W 120

THEFT DELAY WALL MOUNTS



Mount	FSMI	FSMT	FSMT Slim-line
P2691	32S/ 32SP 40S-65S 42SP - 55SP	32-70 32P/42P 47P - 55P/72P	32S - 65S 32SP 42SP- 55SP
P5925	40SP	40P/46P	40SP
P6331	60SP-65SP	60P - 70P	60SP - 65SP
P6441		75 / 75P	

CEILING MOUNTS



Ref.
Tube length



Custom ceiling mount length available on request

FSM-CM600
600 mm

FSM-CM1000
1000 mm

SCREEN-CRAWLER (INSTALLATION AID)



Ref.	SC-190	SC-200
Max load	200 kg	200 kg
Height (retracted)	1990 mm	2200 mm
Max. lift height (hook)	2900 mm	3550 mm



- ▲ Complies with NEN-EN-ISO 12100:210NL
- ▲ Yearly check-up required

